GRAS 43AF

1" 6cc Coupler Kit According to IEC 60318-3





Connection: 200 V/LEMO

Volume: 6 cc

Dyn range: 14 dB(A) to 146 dB

ANSI: S3.7 IEC: 60318-3 The GRAS 43AF Coupler Kit is a complete test jig for acoustically testing telephone handsets and earphones and complies with ANSI S 3.7 – 1995 – American National Standard for Testing Earphones.:



Technology

The GRAS 43AF Coupler Kit is a complete test jig for acoustically testing telephone handsets and earphones and complies with ANSI S 3.7 – 1995 – American National Standard for Testing Earphones.



Specifications

Theoretical dynamic range lower limit with GRAS preamplifier Theoretical dynamic range upper limit with GRAS preamplifier @ dl +28 V / ±14 V power supply Theoretical dynamic range upper limit with GRAS preamplifier @ dl +120 V / ±60 V power supply Set sensitivity @ 250 Hz (±2 dB) mV/ Set sensitivity @ 250 Hz (±2 dB) dB reference many contents of the sensitivity many contents of the sensiti	B B /Pa	14 134 146 50
+28 V / ±14 V power supply Theoretical dynamic range upper limit with GRAS preamplifier @ +120 V / ±60 V power supply Set sensitivity @ 250 Hz (±2 dB) mV,	IB /Pa	146
+120 V / ±60 V power supply Set sensitivity @ 250 Hz (±2 dB) mV,	/Pa	
		50
Sat consitivity @ 250 Hz (+2 dP)		
Set sensitivity @ 250 Hz (12 db)	1V/Pa	-26
Coupler volume mr	m³	6 ccm
Temperature range, operation °C /	/°F	-30 to 60 / -22 to 140
Temperature coefficient @250 Hz dB/°C /	/ dB/°F	-0.01 / -0.006
Humidity range non condensing % F	RH	0 to 80
ANSI standard		S3.7
IEC standard		60318-3 (former 60303)
ITU-T recommondations		P.380
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Connector type		3 m 7-pin LEMO
Weight g /	oz oz	1.75 / 61.729

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



Ordering info

Included

GRAS RA0075	NBS 9A Coupler
GRAS RA0076	Thread Adapter
GRAS 40EN	1" Microphone
GRAS 26AC	¼" Preamplifier
GRAS RA0052	Test Jig

Optional

GRAS 12AK	Power Module
GRAS 42AA	Pistonphone

Miscellaneous

GRAS RA0196	High-tension springs (set of two)

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION

Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.GRASacoustics.com gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION

9290 SW Nimbus Avenue Beaverton, OR 97008 Tel: 503-627-0832 Toll Free: 800-231-7350 www.GRASacoustics.com sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION

Unit 115, Gibson House, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU Tel: +44 (0) 7762 584 202 www.GRASacoustics.com sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION

Room 315, RuiBo Center(T1) Lane683, Shenhong Rd, Minhang District, Shanghai, China, 201107 Tel: +86 21 64203370 www.GRASacoustics.cn cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

GRAS

An Axiometrix Solutions Brand

grasacoustics.com